

| Model | MAC40RII | MAC60RII | MAC80RII | MAC100R |
|--------------------|--|---------------------|---------------------|----------------------|
| Air Flow Volume | 40 L/min 1.4 cfm | 60 L/min 2.1 cfm | 80 L/min 2.8 cfm | 100 L/min 3.5 cfm |
| Normal Pressure | 12 kPa 1.7 PSI | 15 kPa 2.2 PSI | 15 kPa 2.2 PSI | 18 kPa 2.6 PSI |
| Weight | 4.5 kg 9 Lbs. 14 oz. | 5.0 kg 11 Lbs. | 5.0 kg 11 Lbs. | 5.0 kg 11 Lbs. |
| Power Consumption | 30W 0.8A | 47W 1.3A | 51W 1.0A | 74W 1.7A |
| Operating Decibels | 37dB | 37dB | 39dB | 40dB |
| Outlet Pipe Size | 13mm ID (18mm OD) 33/64 inch ID (45/64 inch OD) | | | |
| Rated Voltage | 120V | | | |
| Frequency | 60Hz | | | |
| Power Cable | 3 × 18AWG × 1.8m (5ft.11in.) | | | |
| Manufacturer | Made in Japan | | | |

| Model | MAC120RII | MAC150RII | MAC200RII |
|---------------------------|---|----------------------|----------------------|
| Air Flow Volume | 120 L/min 4.2 cfm | 150 L/min 5.3 cfm | 200 L/min 7.0 cfm |
| Normal Pressure | 18 kPa 2.6 PSI | 20 kPa 2.9 PSI | 20 kPa 2.9 PSI |
| Weight | 5.0 kg 11 Lbs | 9.0 kg 20 Lbs. | 9.0 kg 20 Lbs. |
| Power Consumption | 93 W 1.8A | 115 W 2.3A | 155 W 3.1A |
| Operating Decibels | 41dB | 41dB | 43dB |
| Outlet Pipe Size | 20mm ID (26mm OD) 25/32 inch ID (1-1/32 inch OD) | | |
| Rated Voltage and Current | 120V | | |
| Frequency | 60Hz | | |
| Power Cable | 3 × 18AWG × 1.8m (5ft.11in.) | | |
| Manufacturer | Made in Japan | | |